

Peran OL

Product sheet

Product description

Peran OL is a water based 1-component, un-pigmented acrylic dispersion.

Uses

Peran OL is used as a transparent topcoat for application on walls and coloured flake systems (such as the Peran WA Accent Wall system). It is suitable for use in wet or dry environments where high abrasion & chemical resistance are not important.

Environment & Health

Peran OL is a solvent free product, and practically odourless during application. It is not classified as hazardous to health or environment. Follow the appropriate Occupational Health and Safety guidelines applicable to the location where the application is undertaken.

For more information, please refer to the safety datasheets for the individual components.

Ratio of components

Peran OL is a single component product.

Application temperature

The recommended substrate temperature is 15-25°C, but no less than 10°C. The temperature of the substrate should exceed the "dew point" by 3°C during application and hardening.

Temperatures should not fall below 5°C in the 24 hrs after application.

Curing time (20°C)

Can be overcoated after 1 hour.

Low relative humidity, max 70 %, and good ventilation are prerequisites to achieve the above drying time.

Maximum overcoat time 24 hours.

Colours

Transparent.

Solids content

Approx. 50 %

Finish

Gloss

Density

Approx. 1.06 kg/l.

Storage

12 months in an unopened pack at a temperature of 5-40°C. Protect from frost. Protect from weather and moisture/contaminant ingress.

Packaging

The product is supplied in the following packs:

Unit
12 kg (8.0 litres)

Any suggested practices or installation specifications for the composite floor or wall system (as opposed to individual product performance specifications) included in this communication (or any other) from Flowcrete UK Ltd constitute potential options only and do not constitute nor replace professional advice in such regard. Flowcrete UK Ltd recommends any customer seek independent advice from a qualified consultant prior to reaching any decision on design, installation or otherwise.

UNCONTROLLED COPY